

Agency Information

The certificate is only used for browsing on the web and proves that SETsafe | SETfuse has been certified.

If you need a FULL-VERSION certificate, please contact us: sales@SETfuse.com

该证书只用于在网页浏览，证明SETsafe | SETfuse已获得认证，如需要完整版本证书，请联系我们: sales@SETfuse.com

JDYX8.E345932 - Fuses, Supplemental Certified for Canada - Component

Fuses, Supplemental Certified for Canada - Component

XIAMEN SET ELECTRONICS CO LTD
 8067 XIANG'AN XI RD XIAMEN TORCH
 HIGH-TECH INDUSTRIAL DEVELOPMENT ZONE
 XIANG'AN INDUSTRY DIST
 XIAMEN, FUJIAN 361101 China

E345932

| Cat. No. | Size mm(in) | Amps (A) | Volts (V) | Interrupting Rating (A) |
|---|-------------------------|-----------|-----------|-------------------------|
| SCF632 followed by rated current 300mA, 315mA, 350mA, 400mA, 500mA, 630mA, 700mA, 800mA, 1A, 1.2A, 1.25A, 1.5A, 1.6A, 2A, 2.25A, 2.5A, 3A, 3.15A, 3.5A, 4A, 5A, 6A, 6.3A, 7A, 8A, 9A, 10A, 12A, 12.5A, 15A, 16A, 20A, 25A, 21A or 30A. | 32 x 6.35 (1.26 x 0.25) | 0.3- 12.5 | 125Vdc | 50000 |
| | | 0.3- 12.5 | 250Vdc | 50000 |
| | | 0.3- 12.5 | 300Vdc | 50000 |
| | | 0.3- 12.5 | 350Vdc | 50000 |
| | | 0.3- 12.5 | 400Vdc | 50000 |
| | | 0.3- 12.5 | 450Vdc | 50000 |
| | | 0.3- 12.5 | 500Vdc | 50000 |
| | | 0.3- 12.5 | 600Vdc | 50000 |
| | | 0.3- 12.5 | 125Vac | 10000 |
| | | 0.3- 12.5 | 250Vac | 10000 |
| | | 0.3- 12.5 | 300Vac | 10000 |
| | | 0.3- 12.5 | 350Vac | 10000 |
| | | 0.3- 12.5 | 400Vac | 10000 |
| | | 0.3- 12.5 | 450Vac | 10000 |
| | | 0.3- 12.5 | 500Vac | 10000 |
| | | 0.3- 12.5 | 600Vac | 10000 |
| | | 15-30 | 125Vdc | 1000 |
| | | 15-30 | 250Vdc | 1000 |
| | | 15-30 | 300Vdc | 1000 |
| | | 15-30 | 350Vdc | 1000 |
| | | 15-30 | 400Vdc | 1000 |
| | | 15-30 | 450Vdc | 1000 |
| | | 15-30 | 500Vdc | 1000 |
| | | 15-30 | 600Vdc | 1000 |
| | | 15-30 | 125Vac | 1000 |
| | | 15-30 | 250Vac | 1000 |
| | | 15-30 | 250Vac | 1500 |
| | | 15-30 | 300Vac | 1000 |
| | | 15-30 | 350Vac | 1000 |
| | | 15-30 | 400Vac | 1000 |
| | | 15-30 | 450Vac | 1000 |
| | | 15-30 | 500Vac | 1000 |
| | | 15-30 | 600Vac | 1000 |
| Supplemental fuses: pigtail leads, filled-tube, cartridge enclosed | | | | |
| SCF632P followed by rated current 300mA, 315mA, 350mA, 400mA, 500mA, 630mA, 700mA, 800mA, 1A, 1.2A, 1.25A, 1.5A, 1.6A, 2A, 2.25A, 2.5A, 3A, 3.15A, 3.5A, 4A, 5A, 6A, 6.3A, 7A, 8A, 9A, 10A, 12A, 12.5A, 15A, 16A, 20A, 21A, 25A or 30A. | 32 x 6.35 (1.26 x 0.25) | 0.3- 12.5 | 125Vdc | 50000 |
| | | 0.3- 12.5 | 250Vdc | 50000 |
| | | 0.3- 12.5 | 300Vdc | 50000 |
| | | 0.3- 12.5 | 350Vdc | 50000 |

| | | | | |
|--|--|-----------|--------|-------|
| | | 0.3- 12.5 | 400Vdc | 50000 |
| | | 0.3- 12.5 | 450Vdc | 50000 |
| | | 0.3- 12.5 | 500Vdc | 50000 |
| | | 0.3- 12.5 | 600Vdc | 50000 |
| | | 0.3- 12.5 | 125Vac | 10000 |
| | | 0.3- 12.5 | 250Vac | 10000 |
| | | 0.3- 12.5 | 300Vac | 10000 |
| | | 0.3- 12.5 | 350Vac | 10000 |
| | | 0.3- 12.5 | 400Vac | 10000 |
| | | 0.3- 12.5 | 450Vac | 10000 |
| | | 0.3- 12.5 | 500Vac | 10000 |
| | | 0.3- 12.5 | 600Vac | 10000 |
| | | 15-30 | 125Vdc | 1000 |
| | | 15-30 | 250Vdc | 1000 |
| | | 15-30 | 300Vdc | 1000 |
| | | 15-30 | 350Vdc | 1000 |
| | | 15-30 | 400Vdc | 1000 |
| | | 15-30 | 450Vdc | 1000 |
| | | 15-30 | 500Vdc | 1000 |
| | | 15-30 | 600Vdc | 1000 |
| | | 15-30 | 125Vac | 1000 |
| | | 15-30 | 250Vac | 1000 |
| | | 15-30 | 250Vac | 1500 |
| | | 15-30 | 300Vac | 1000 |
| | | 15-30 | 350Vac | 1000 |
| | | 15-30 | 400Vac | 1000 |
| | | 15-30 | 450Vac | 1000 |
| | | 15-30 | 500Vac | 1000 |
| | | 15-30 | 600Vac | 1000 |