

Description

Thermal-Link (ATCO)-Alloy Type is defined as a non-resettable protective device functioning one time only. It is widely used in electrical equipment. ATCO is mainly consist of fusible alloy, flux resin, case, sealant and lead wires. Normally, fusible alloy is jointed to the two lead wires. Under abnormal conditions, when the temp. reaches to the fusing temp. of ATCO, the fusible alloy melts and quickly retracts to the two lead wire ends with the aid of the flux resin and disconnects the circuit completely.

SETsafe | SETfuse Thermal-Link (ATCO)-Alloy Type Q series Rated Functioning Temp. from 102 °C to 136 °C, Rated Current: 25A, safety certification Includes UL, cUL, TUV, CCC, PSE, and complies with RoHS and REACH.

Features

- Non-Resettable
- High Accuracy of Functioning Temp.
- High Surge Capacity
- RoHS & REACH Compliant

Applications


- Surge Protective Devices
- Power Strips
- Lamps
- Switched-Mode Power Supplies
- Home Electrical Appliances
- Batteries

Customization

- Other Temp.
- The Length of Lead Wires
- Leads Forming Types


Structure Diagrams

Radial




Marking

Radial (Color for reference only)



Remark: The Date Code means Year and quarter: A stands for 2000, B stands for 2001 and 01 stands for the first quarter, 02 stands for the second quarter, and so on.






Dimensions (mm)



L	L ₁	W	T	d	F
11.5 ± 0.5	50.0 ± 2.0	10.8 ± 0.5	4.8 ± 0.2	1.60 ± 0.05	6.6 ± 0.8

Specifications

Rated Functioning Temp. (T_f) °C

	Model	Fusing Temp.	T _h	T _m	I _r	U _r	I _n 8 / 20 μs (15 Times)	I _{max} 8 / 20 μs (1 Time)						RoHS REACH
		(°C)	(°C)	(°C)	(A)	(V)	(kA)	(kA)	UL	cUL	TUV	PSE	CCC	
136	Q136	131 ± 2	102 92 ^a	200	25	AC 250	15	30	●	●	○	●	○	●
						AC 300			●	●	○	●	○	●
						AC 400			○	○	●	●	●	●
						DC 120			○	○	●	○	●	●
125	Q125	121 ± 2	90 80 ^a	200	25	AC 250	15	30	○	○	○	●	○	●
						AC 400			○	○	●	●	●	●
						DC 120			○	○	●	○	●	●
115	Q115	111 ± 2	82 72 ^a	200	25	AC 250	15	30	●	●	○	●	○	●
						AC 300			●	●	○	●	○	●
						AC 400			○	○	●	●	●	●
						DC 120			○	○	●	○	●	●
102	Q102	98 ± 2	66 50 ^a	200	25	AC 250	12	25	○	○	○	●	○	●
						AC 400			○	○	●	●	●	●
						DC 120			○	○	●	○	●	●






Note:

1: "●"Means certificated, "○"Means non-certificated.

2: RoHS & REACH Compliant .

3: " a ": The temperature measurement point for holding temperature (T_h) shall be positioned 50 mm away from the product body, in accordance with the requirements specified in Appendix I of GB/T 9816.1-2023.

Agency Information

Agency Symbol	Standards	The File No. and certification No. obtained by SETsafe SETfuse
	UL 60691	E214712
	CAN-CSA-E60691	E214712
	EN 60691	R50259029
	J60691	JET2121-32001-2032, JET2121-32001-2033
	GB 9816.1	2020980205000180

Soldering

Hand-Soldering

1. Soldering should be carried out according to Table T-1.
2. The thermal element of ATCO is fusible alloy with low melting point, which is jointed with ATCO lead wires. Improper soldering operation (too high soldering temp. , too long soldering time, too short lead wire etc.) may transfer more heat to the thermal element and ATCO may open in advance.
3. When soldering conditions are more severe than those listed in Table T-1, a heat sink fixture should be used between soldering point and ATCO body.
4. When soldering, please do not pull / push or twist ATCO body or lead wires.
5. After soldering, let it naturally cool for longer than 20 seconds. During cooling, never move the ATCO body or lead wires.




FIGURE T-1

TABLE T-1 Hand-Soldering Time

Rated Functioning Temp. (<i>T_f</i>)	Max. Allowable Soldering Time for Different Lead Wire Length (Fig.T-1)									Max. Soldering Temp.
	L _s Length	Time		L _s Length	Time		L _s Length	Time		
		Tinned Copper Wire	CP Wire		Tinned Copper Wire	CP Wire		Tinned Copper Wire	CP Wire	
(°C)	(mm)	(s)	(s)	(mm)	(s)	(s)	(mm)	(s)	(s)	(°C)
102 to 115	10	1 ^a	4	20	2	5	30	3	6	400
116 to 135	10	1 ^a	4	20	3	6	30	5	8	
136 to 150	10	3	6	20	5	8	30	5	8	

Note:


a: Auxiliary Heat Sink Fixture is Required to Avoid ATCO Cutting off Unexpectedly.

Wave Soldering

The wave soldering parameters as Table T-2, for reference only, when ATCO is for practice use, you need to do some validation experiments. For example, using X-RAY to see the fusible alloy of ATCO whether damage after wave soldering.


TABLE T-2 Wave Soldering Parameters Setting

Rated Functioning Temp. (T_f)	Max. Allowable Preheating Temp. When the Length of Lead Wire is Different (Fig.T-1)				Preheating Time (t_1)	Max. Wave Soldering Temp.	Dwelling Time (t_2)	Cooling Time (t_3)
	L_s Length	Preheating Temp.	L_s Length	Preheating Temp.				
(°C)	(mm)	(°C)	(mm)	(°C)	(s)	(°C)	(s)	(s)
102 to 130	Recommend Hand-Soldering							
131 to 150	20	80	30	90	< 60	≤ 260	≤ 3	≤ 10




Product Temp.-Time Curve (Reference)

The Temp.-Time Curve of Thermal-Link in different temp. oil bath.



Product Current-Time Curve (Reference)


The Current-Time Curve shows functioning time at multi-times rated current at room temperature $25 \pm 2^\circ\text{C}$.



Packaging Information

Bulk

Item	PE Bag	PE Bag	Carton
Dimensions (mm)	135 × 85	190 × 180	440 × 300 × 260
Quantity (PCS)	30	180	9000
Gross Weight (kg)	24.0 ± 10%		



Part Numbering System

ATCO – Q 115 – A N N A B – 001

Other Options

Packing

- B Bulk
- T Taping

Leads Forming

- A Straight Lead
- B Single Lead Bending
- C Leads Bending
- D Leads Kinking
- E Leads Bending and Kinking

Color of Insulation Tube

- W White
- Y Yellow
- R Red
- K Black
- N None

Insulation Tube Material

- T Teflon
- P Polyester
- N None

Lead Wire Type

- A Tinned Copper Wire
- B Tinned Copper Plated Wire

Rated Functioning Temp.

- 115 115 °C, See Specifications

Series

- Q Series
See Specifications

Product Category

ATCO Alloy Thermal-Link

Glossary

Item	Description
TCO	Thermal-Link A non-resettable device incorporating a THERMAL ELEMENT which will open a circuit once only when exposed for a sufficient length of time to a temperature in excess of that for which it has been designed. — (GB 9816.1)
ATCO	Alloy Thermal-Link Alloy Type Thermal-Link, Alloy is the thermal element. — (GB 9816.1)
T_f	Rated Functioning Temp. The temperature of the Alloy Thermal-Link which causes it to change the state of conductivity with a detection current up to 10 mA as the only load. — (GB 9816.1) Tolerance: T_f °C (GB 9816.1, EN 60691, K60691). Tolerance: $T_f \pm 7$ °C (J60691).
Fusing Temp.	Fusing Temp. The temperature of the Alloy Thermal-Link which causes it to change its state of conductivity is measured with silicone oil bath in which the temperature is increased at the rate of 0.5 °C to 1 °C / minute, with a detection current up to 10 mA as the only load. — (GB 9816.1)
T_h	Holding Temp. The Maximum temperature at which a Alloy Thermal-Link will not change its state of conductivity when conducting rated current for 168 hours. — (GB 9816.1)
T_m	Maximum Temp. Limit The temperature of the Alloy Thermal-Link stated by the manufacturer, up to which the mechanical and electrical properties of the Alloy Thermal-Link having changed its state of conductivity, will not be impaired for a given time. — (GB 9816.1)
I_r	Rated Current The current used to classify a Alloy Thermal-Link, which is the Maximum current that Alloy Thermal-Link allows to carry and is able to cut off the circuit safely. — (GB 9816.1)
U_r	Rated Voltage The voltage used to classify a Alloy Thermal-Link, which is the Maximum voltage that Alloy Thermal-Link allows to carry and is able to cut off the circuit safely. — (GB 9816.1)
I_n	Nominal Discharge Current Being able to withstand 15 peak currents of waveform 8/20 μ s to test the product's durability of withstanding pulse current. — (UL 1449)
I_{max}	Max. Discharge Current Being able to withstand 1 peak current of waveform 8/20 μ s to test max. pulse current that the product can withstand. — (UL 1449)



ATTENTION

Usage

1. When atmosphere pressure is from 80 kPa to 106 kPa, the related altitude shall be from 2000 meters to - 500 meters.
2. Operating voltage less than rated voltage of ATCO, operating current less than rated current of ATCO.
3. Do not touch the ATCO body or lead wires directly when power is on, to avoid burn or electric shock.

Replace

ATCO is a non-repairable product. For safety sake, it shall be replaced by an equivalent ATCO from the same manufacturer, and mounted in the same way.

Storage

Do not store the ATCO at the high temp., high humidity or corrosive gas environment, avoid influencing the solder-ability of the lead wires, the product shall be used up within 1 year after receiving the goods.

Installation

Make Sure the Temp. of Installation Position.

1. It is recommended that a dummy ATCO with inbuilt thermo-couple shall be used to determine the proper temp.
2. The terminal product should be tested to ensure that potential abnormal conditions do not cause ambient temp. to exceed the T_m of the ATCO.
3. Mount the ATCO at the location where temp. rises evenly.

Installation position of mechanical performance requirements.

1. Do not locate the ATCO in a place where severe vibration always occurs.
2. Ensure that the lead wire is long enough, and avoid actions such as press, tensile or twist.
3. The seal or body of ATCO must not be damaged, burned or over heated.

Mechanical Connection

Riveting

1. Choose small resistivity riveting material and be riveted.
2. A flexible lead or lead with low resistance should be used to rivet the ATCO.
3. Contact resistance should be minimal, large contact resistance will lead to higher temp., ATCO Functioning in advance.

Crimping

1. Choose small resistivity crimping material and be crimped.
2. A flexible lead or lead with low resistance should be used to rivet the ATCO.
3. Contact resistance should be minimal, large contact resistance will lead to higher Temp., ATCO Functioning in advance.

Lead Wire Forming

1. If lead wire has to be bent, please pay attention to the distance between body and bending point. Refer to Table T-3.
2. When bending leads, please use pincher or similar tools to fix the product as shown in Fig.T-2, to avoid damaging the product.
3. During forming and mounting, lead wire should not be cut, nicked, bent sharply, to avoid breaking the product.
4. Tangential forces on the leads must be avoided (i.e. pushing or pulling on the leads at angle to ATCO body) as such forces may damage the seal of ATCO.




FIGURE T-2

TABLE T-3 Distance between Body and Bending Point

	d	(mm)	< 1.0	1.0 - 1.2	> 1.2
	L _b	(mm)	≥ 3	≥ 5	≥ 10
Circular lead					

Thermal-Link (ATCO)-Alloy Type Feature & Model List Overview

[illegible]


Thermal-Link (ATCO)-Alloy Type

Q Series




Thermal-Link (ATCO)-Alloy Type Feature & Model List Overview

Rated Functioning Temp. (T _f) °C	Model																								Product Structure
	230	221	205	200	187	160	150	145	139	136	135	133	130	125	123	120	115	105	102	97	95	86	76		
I _r (A) Rated Current	10	15	2	3	5	5	10	15	16	25	2	3	3	5	5	10	15	16	25	2	3	2	3	10	
	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	
U _r (VAC) Rated Voltage	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	
	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	
Product Structure	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	
	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	Cylindrical	
Product Structure	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	
	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	Radial Shape	
Product Structure	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	
	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	320	
Product Structure	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	
	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	400	
Product Structure	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	
	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500	
Product Structure	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	
	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	690	
Product Structure	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	
	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	800	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	
	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	AXIAL SHAPE (Flat Electrode)	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	
Product Structure	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE	AXIAL SHAPE										

Thermal-Link (ATCO)-Alloy Type Feature & Model List Overview

Rated Functioning Temp. (T _f) °C	Model																				Product Structure		Axial Shape																	
	1	2	3	5	7	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80				85	90	95	100	105	110	115	120	125	130	135	140	145	150	160	187	200
I _r (A) Rated Current	1	2	3	5	7	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145	150	160	187	200	205	221	230
U _r (VDC) Rated Voltage	1	2	3	5	7	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145	150	160	187	200	205	221	230

Thermal-Link (ATCO)-Alloy Type Feature & Model List Overview

Rated Functioning Temp. (T _r) °C	Model																								Product Structure																												
	230	221	205	200	187	160	150	145	139	136	135	133	130	125	123	120	115	105	102	97	95	86	76																														
I _r (A) Rated Current	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2																														
	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3																														
U _r (VDC) Rated Voltage	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60																														
	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100																														
Product Structure	Radial Shape (Screw Hole)												Radial Shape												Axial Shape (Flat Electrode)																												
																																																					
																								125										200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			
																								5 25										10 10																			
																								20 125										5 200																			
																								15 16										20 25																			
																								10 50										15 16																			