


Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube



Dimensions (mm)



L	L ₁	L ₂	D	d
20.0 ± 0.5	5.1 ± 0.3	96 ± 2	Φ5.2 ^{+0.1/-0.2}	≤6.3 A: Φ(0.65 ± 0.05) >6.3 A to 10 A: Φ(0.80 ± 0.05) >10 A to 20 A: Φ(1.00 ± 0.05) 25 A: Φ(1.20 ± 0.05)

Description

Φ5 × 20 mm, Fast Acting, high breaking capacity cartridge fuse, designed to IEC, GB/T and UL standards.

Key Features

- Body Size: Φ5 × 20 mm
- Fast Acting
- High Breaking Capacity
- Ceramic Tube, Nickel-plated Brass End Cap Construction
- Designed to UL248-14 / IEC 60127-7 / GB/T 9364.7
- Lead-free (Pb-free)
- RoHS and REACH Compliant

Applications

- Power Supply
- Household Appliance
- General Lighting
- Smart Home
- Office Equipment
- Electric Tool
- Medical Equipment
- Instruments and Apparatuses

Time/Current Characteristic

% of Ampere Rating	Ampere Rating	Opening Time
210%	0.4 A ~ 25 A	30 minutes, Max.
275%	0.4 A ~ 25 A	0.04 s ~ 20 s
400%	0.4 A ~ 25 A	0.01 s ~ 10 s
1000%	0.4 A ~ 10 A	0.03 s, Max.
	12 A ~ 25 A	0.08 s, Max.

Product Number System

SCF520F20A250V

Rated Voltage


Rated Current

Product Series

SCF520: Cartridge Type

SCF520P: Axial Lead Type

Structure



Agency Approvals

Agency Symbol	The file No. and certification No. obtained by SETsafe SETfuse	Ampere Range
	E345932	0.5 A ~ 25 A
	CQC21012313736 CQC21012313738 CQC21012317022 CQC21012317866 CQC21012319112 CQC21012320077 CQC21012322189 CQC21012322191	0.4 A ~ 20 A
	R 50541719 J 50689680	1 A ~ 20 A

Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Specifications

Series	Rated Current	Rated Breaking Capacity	Average Typical Melting I^2t^a	Agency Approvals			Environmental	
	(A)			 CQC	 TUV	 cURus	RoHS	REACH
SCF520(P)	0.4	UL (0.5 A-10 A): 1500 A@300 VAC 300 A@500 VAC / DC UL (12 A-25 A): 1500 A@300 VAC 300 A@500 VAC 300 A@420 VDC	0.06	●	○	○	●	●
SCF520(P)	0.5		0.14	●	○	●	●	●
SCF520(P)	0.63		0.23	●	○	●	●	●
SCF520(P)	0.8		0.4	●	○	●	●	●
SCF520(P)	1		0.6	●	●	●	●	●
SCF520(P)	1.25		1.0	●	●	●	●	●
SCF520(P)	1.6		1.4	●	●	●	●	●
SCF520(P)	2		3.8	●	●	●	●	●
SCF520(P)	2.5		4.8	●	●	●	●	●
SCF520(P)	3.15		8.5	●	●	●	●	●
SCF520(P)	4		17	●	●	●	●	●
SCF520(P)	5		34	●	●	●	●	●
SCF520(P)	6.3		65	●	●	●	●	●
SCF520(P)	8		114	●	●	●	●	●
SCF520(P)	10		240	●	●	●	●	●
SCF520(P)	12.5		310	●	●	●	●	●
SCF520(P)	15		320	○	○	●	●	●
SCF520(P)	16		480	●	●	●	●	●
SCF520(P)	20		1250	●	●	●	●	●
SCF520(P)	25		2000	○	●	●	●	●

Remark:

a: I^2t value is measured at 10 I_N.

○: Pending, RoHS and REACH Compliant

Breaking Capacity (CQC/TUV):

SCF520 (0.4 A / 0.5 A / 0.63 A / 1 A / 1.6 A / 2 A / 2.5 A / 3.15 A / 5 A): 5000 A@250 VAC /DC, 300 A@600 VAC / DC, 3000 A@300 VAC

SCF520 (0.8 A / 1.25 A / 4 A / 6.3 A / 12.5 A / 16 A): 5000 A@250 VAC / DC, 300 A@600 VDC, 3000 A@300 VAC, 200 A@500 VAC

SCF520 (10 A): 5000 A@250 VAC / DC, 300 A@500 VAC / DC, 3000 A@300 VAC

SCF520 (20 A): 5000 A@250 VDC, 200 A@350VAC

SCF520P (0.4 A / 0.8 A / 1 A / 4 A / 5 A / 6.3 A / 8 A / 10 A): 5000 A@250 VAC / DC, 300 A@600 VDC, 3000 A@300 VAC, 300 A@500 VAC

SCF520P (0.5 A / 0.63 A / 1.25 A / 1.6 A / 2 A / 2.5 A / 3.15 A): 5000 A@250 VAC / DC, 300 A@600 VAC / DC, 3000 A@300 VAC

SCF520P (12.5 A / 16 A): 5000 A@250 VAC / DC, 300 A@600 VDC, 3000 A@300 VAC, 200 A@420 VAC

SCF520P (20 A): 5000 A@250 VDC, 200 A@350VAC


SCF520P (25 A): 1500 A@250 VAC, 300 A@420 VDC / 350 VDC / 300 VDC / 250 VDC / 125 VDC。

Miniature Fuses


Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Time Current Curve (For Reference Only)



Rated Current Derating Curve (For Reference Only)




Miniature Fuses

Cartridge Fuse-links (CFL)


SCF520(P) Series, Fast Acting Ceramic Tube

Packaging Information


Dimensions (mm)




Cartridge Type		
Item	PE Bag	Carton
Q'ty (PCS)	1,000	10,000
Gross Weight (kg)		13.5×(1±10%)



Axial Lead Type			
Item	PE Bag	Box	Carton
Q'ty (PCS)	400	800	8,000
Gross Weight (kg)		15.5×(1±10%)	



Bending Molding Type (Vertical or Horizontal)			
Item	PE Bag	Box	Carton
Q'ty (PCS)	500	1,000	10,000
Gross Weight (kg)		14.8×(1±10%)	



Taping Type		
Item	Box	Carton
Q'ty (PCS)	800	8,000
Gross Weight (kg)		14.5×(1±10%)



ATTENTION

Inspection

Cold Resistance Test

- a. Applied current shall be less than 10% of rated current, at ambient Temp. of $(23 \pm 2) ^\circ\text{C}$.
- b. 4-Wire Resistance Measurement.

Usage

- a. Do not touch the fuse body or lead wire when power on, avoiding scald or electric shock.
- b. The air pressure is 80 kPa to 106 kPa, corresponding to the altitude of +2000 m to -500 m.

Replacement

For safety reasons, the Fuse is a non-resettable product, please ensure that the alternative Fuse is the same type when replace it.

Storage

Fuse storage should avoid high temperature, high humidity, direct sunlight, and corrosive gases, so as not to affect the solderability of the lead wire. Please use them up within 1 year after receiving the goods.

Installation

Do not apply mechanical stress to the fuse body during or after the installation.

Installation Position

Do not install the fuse on an assembly that may often subject to severe continuous vibration or with corrosive gases (NH_3 , SO_2 , Cl_2 etc.).


Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Soldering Parameters

Wave soldering Parameters (For Reference Only)



Item	Temp. (°C)	Time (second)
Preheating	100 ~ 150	60 ~ 180
Dwelling	255 ~ 265	4 ~ 8

Recommended Soldering Parameters

Solder Iron Temp.: (350 ± 5) °C

Soldering Time: 5 seconds, Max.

Lead Wire Bending

If the lead wire has to be bent, please pay attention to the distance between body and the bending point. Refer to the following table.

Axial Type			
d	≤ Φ 1.0 mm	> Φ 1.0 mm	
L	≥ 3 mm	≥ 5 mm	

Glossary

Item	Description
Fuse	A device, by the fusing of one or more of its specially designed and proportioned components, opens the circuit in which it is inserted by breaking the current when this exceeds a given value for a sufficient time. —(IEC 60127)
Rated Current	The rated current of a fuse identifies its current-carrying capacity based on a controllable set of test conditions. Each fuse is marked with its rated current, this rating can be identified with a numeric, alpha, or color code mark. —(IEC 60127)
Rated Voltage	A Max. open circuit voltage in which a fuse can be used, yet safely interrupt an overcurrent. Exceeding the voltage rating of a fuse impairs its ability to clear an overload or short circuit safely. —(IEC 60127)
Ampere Squared Seconds I^2t	The melting, arcing, or clearing integral of a fuse, termed I^2t, is the thermal energy required to melt, arc, or clear a specific current. It can be expressed as melting I^2t, arcing I^2t or the sum of them, clearing I^2t. —(IEC 60127)
Overload	Can be classified as an overcurrent which exceeds the normal full load current of a circuit by 2 to 5 times its magnitude and stays within the normal current path. —(UL 248)
Overcurrent	A condition which exists in an electrical circuit when the normal load current is exceeded. Overcurrent take on two separate characteristics-overloads and short circuits. —(UL 248)
Short Circuit	An overcurrent that leaves the normal current path and greatly exceeds the normal full load current of the circuit by a factor of tens, hundreds, or thousands times. —(UL 248)
Breaking Capacity of a Fuse-link	Value (r.m.s. for AC) of prospective current that a fuse-link is capable of breaking at a stated voltage under prescribed conditions of use and behaviour. —(IEC 60127)

Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Reliability Test



No.	Items	Inspection Standards	Standards
1	High Temp. Test	Test Condition: Temperature: (105 ± 2) °C Time: 1000 hours Test Requirement: After the test, the voltage drop shall not have changed by more than 10% of the value measured before the test. The clearing time of the fuse shall be in range.	MIL-STD-202(Test Method 108) GJB360B(Test Method 108)
2	High Humidity Test	Test Condition: Temperature: (40 ± 2) °C Humidity: 90% to 95% Time: 96 hours Test Requirement: After the test, the voltage drop shall not have changed by more than 10 % of the value measured before the test. The clearing time of the fuse shall be in range.	MIL-STD-202(Test Method 103) GJB360B(Test Method 103)
3	Thermal Shock Test	Test Condition: Per Cycle: -55 °C / 30 minutes, 125 °C / 30 minutes Time: 100 Cycles Test Requirement: After the test, the voltage drop shall not have changed by more than 10 % of the value measured before the test. The clearing time of the fuse shall be in range.	MIL-STD-202(Test Method 107) GJB360B(Test Method 107)

Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Cartridge Fuse-links (CFL) Features & Model List Overview


Rated Current I_n (A)	50.00	SCF625F50A	SCF625PF50A	○	○	○	Model Remark: Please refer to each product series specification page for complete models
	40.00	SCF625F40A	SCF625PF40A	○	○	○	
	30.00	SCF625F30A	SCF625PF30A	○	○	○	
	25.00	SCF625F25A	SCF625PF25A	○	○	○	
	21.00	○	○	○	○	○	
	20.00	SCF625F20A	SCF625PF20A	○	SGF520-20A (-L)	SGT520-20A (-L)	
	16.00	SCF625F16A	SCF625PF16A	○	SGF520-16A (-L)	SGT520-16A (-L)	
	15.00	SCF625F15A	SCF625PF15A	○	SGF520-15A (-L)	SGT520-15A (-L)	
	13.00	○	○	SC625FM13A	○	○	
	12.50	SCF625F12.5A	SCF625PF12.5A	○	SGF520-12.5A (-L)	SGT520-12.5A (-L)	
	12.00	SCF625F12A	SCF625PF12A	○	SGF520-12A (-L)	SGT520-12A (-L)	
	10.00	SCF625F10A	SCF625PF10A	SC625FM10A	SGF520-10A (-L)	SGT520-10A (-L)	
	8.00	SCF625F8A	SCF625PF8A	○	SGF520-8A (-L)	SGT520-8A (-L)	
	7.00	○	○	SC625FM7A	○	○	
	6.30	SCF625F6.3A	SCF625PF6.3A	○	SGF520-6.3A (-L)	SGT520-6.3A (-L)	
	6.00	SCF625F6A	SCF632PF6A	○	○	○	
	5.00	SCF625F5A	SCF625PF5A	SC625FM5A	SGF520-5A (-L)	SGT520-5A (-L)	
	4.00	○	○	○	SGF520-4A (-L)	SGT520-4A (-L)	
	3.15	○	○	○	SGF520-3.15A (-L)	SGT520-3.15A (-L)	
	3.00	○	○	SC625FM3A	○	○	
	2.50	○	○	○	SGF520-2.5A (-L)	SGT520-2.5A (-L)	
	2.00	○	○	○	SGF520-2A (-L)	SGT520-2A (-L)	
	1.60	○	○	○	SGF520-1.6A (-L)	SGT520-1.6A (-L)	
	1.25	○	○	○	SGF5201.25A (-L)	SGT520-1.25A (-L)	
	1.00	○	○	○	SGF520-1A (-L)	SGT520-1A (-L)	
	0.80	○	○	○	SGF520-800mA (-L)	SGT520-800mA (-L)	
	0.63	○	○	○	SGF520-630mA (-L)	SGT520-630mA (-L)	
	0.50	○	○	○	SGF520-500mA (-L)	SGT520-500mA (-L)	
	0.40	○	○	○	○	○	
	0.315	○	○	○	○	○	
	0.25	○	○	○	○	○	
	0.20	○	○	○	○	○	
	0.16	○	○	○	○	○	
	0.125	○	○	○	○	○	
	0.10	○	○	○	○	○	
U_r Rated Voltage	(VAC) (VDC)	250 VAC (75 ~ 400) VDC		264 VAC	250 VAC		
Time Feature		Fast Acting		Medium-Acting	Fast Acting	Time-Lag	
Tube Material		Ceramic		Ceramic	Glass		
Standards		UL		IEC / BS	IEC / UL		
Breaking Capacity		300 A ~ 10 kA		6 kA	35 A ~ 200 A		
Physical Size (mm)		Φ6.35 × 25.4		Φ6.35 × 25.4	Φ5 × 20		
Product Structure							

Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Cartridge Fuse-links (CFL) Features & Model List Overview


Rated Current I_n (A)	Model				Remark: Please refer to each product series specification page for complete models
	SCF520F	SCF520PF	SCT520T	SCT520PT	
50.00					
40.00					
30.00			SCT520T30A	SCT520PT30A	
25.00	SCF520F25A	SCF520PF25A	SCT520T25A	SCT520PT25A	
21.00					
20.00	SCF520F20A	SCF520PF20A	SCT520T20A	SCT520PT20A	
16.00	SCF520F16A	SCF520PF16A	SCT520T16A	SCT520PT16A	
15.00	SCF520F15A	SCF520PF15A	SCT520T15A	SCT520PT15A	
13.00					
12.50	SCF520F12.5A	SCF520PF12.5A	SCT520T12.5A	SCT520PT12.5A	
12.00	SCF520F12A	SCF520PF12A	SCT520T12A	SCT520PT12A	
10.00	SCF520F10A	SCF520PF10A	SCT520T10A	SCT520PT10A	
8.00	SCF520F8A	SCF520PF8A	SCT520T8A	SCT520PT8A	
7.00					
6.30	SCF520F6.3A	SCF520PF6.3A	SCT520T6.3A	SCT520PT6.3A	
6.00					
5.00	SCF520F5A	SCF520PF5A	SCT520T5A	SCT520PT5A	
4.00	SCF520F4A	SCF520PF4A	SCT520T4A	SCT520PT4A	
3.15	SCF520F3.15A	SCF520PF3.15A	SCT520T3.15A	SCT520PT3.15A	
3.00	SCF520F3A	SCF520PF3A	SCT520T3A	SCT520PT3A	
2.50	SCF520F2.5A	SCF520PF2.5A	SCT520T2.5A	SCT520PT2.5A	
2.00	SCF520F2A	SCF520PF2A	SCT520T2A	SCT520PT2A	
1.60	SCF520F1.6A	SCF520PF1.6A	SCT520T1.6A	SCT520PT1.6A	
1.25	SCF520F1.25A	SCF520PF1.25A	SCT520T1.25A	SCT520PT1.25A	
1.00	SCF520F1A	SCF520PF1A	SCT520T1A	SCT520PT1A	
0.80	SCF520F800mA	SCF520PF800mA	SCT520T800mA	SCT520PT800mA	
0.63	SCF520F630mA	SCF520PF630mA	SCT520T630mA	SCT520PT630mA	
0.50	SCF520F500mA	SCF520PF500mA	SCT520T500mA	SCT520PT500mA	
0.40	SCF520F400mA	SCF520PF400mA	SCT520T400mA	SCT520PT400mA	
0.315					
0.25					
0.20					
0.16					
0.125					
0.10					
U_r (VAC) Rated Voltage (VDC)	(125 ~ 600) VAC (125 ~ 600) VDC		(125 ~ 500) VAC (125 ~ 500) VDC		
Time Feature	Fast Acting		Time-Lag		
Tube Material	Ceramic				
Standards	IEC / UL				
Breaking Capacity	200 A ~ 5 kA		200 A ~ 10 kA		
Physical Size (mm)	Φ5 × 20				
Product Structure					

Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Sub-miniature Fuse-links (SFL) Feature & Model List Overview

Rated Current I_n (A)			Model
50.00	○		○
40.00	○		○
30.00	○		○
25.00	○		○
21.00	○		○
20.00	○		SPT478T20A
16.00	○		SPT478T16A
15.00	○		SPT478T15A
13.00	○		○
12.50	○		SPT478T12.5A
12.00	○		○
10.00	SPF478F10A		SPT478T10A
8.00	SPF478F8A		SPT478T8A
7.00	○		○
6.30	SPF478F6.3A		SPT478T6.3A
6.00	○		○
5.00	SPF478F5A		SPT478T5A
4.00	SPF478F4A		SPT478T4A
3.15	SPF478F3.15A		SPT478T3.15A
3.00	○		○
2.50	SPF478F2.5A		SPT478T2.5A
2.00	SPF478F2A		SPT478T2A
1.60	SPF478F1.6A		SPT478T1.6A
1.25	SPF478F1.25A		SPT478T1.25A
1.00	SPF478F1A		SPT478T1A
0.80	○		SPT478T800mA
0.63	○		SPT478T630mA
0.50	○		SPT478T500mA
0.40	○		SPT478T400mA
0.315	○		SPT478T315mA
0.25	○		SPT478T250mA
0.20	○		SPT478T200mA
0.16	○		SPT478T160mA
0.125	○		SPT478T125mA
0.10	○		SPT478T100mA
U_r (VAC) Rated Voltage (VDC)	(125 ~ 400) VAC		
Time Feature	Fast Acting		Time-Lag
Tube Material	Plastic Case		
Standards	IEC / UL		
Breaking Capacity	35 A ~ 200 A		
Physical Size (mm)	4 × 7 × 8		
Product Structure			

Remark: Please refer to each product series specification page for complete models

Remark: Please refer to each product series specification page for complete models

Miniature Fuses

Cartridge Fuse-links (CFL)

SCF520(P) Series, Fast Acting Ceramic Tube

Surface Mount Fuse-lings (SMFL) Feature & Model List Overview

Rated Current I_n (A)	Model			
	Remark: Please refer to each product series specification page for complete models			
50.00	○	○	○	○
40.00	○	○	SCF1032F40A	○
30.00	○	○	SCF1032F30A	○
25.00	○	○	SCF1032F25A	○
21.00	○	○	○	○
20.00	SCF6125F20A	○	SCF1032F20A	○
16.00	SCF6125F16A	○	SCF1032F16A	○
15.00	SCF6125F15A	○	SCF1032F15A	SCT1032T15A
13.00	○	○	○	○
12.50	SCF6125F12.5A	SCT6125T12.5A	SCF1032F12.5A	SCT1032T12.5A
12.00	SCF6125F12A	SCT6125T12A	SCF1032F12A	SCT1032T12A
10.00	SCF6125F10A	SCT6125T10A	SCF1032F10A	SCT1032T10A
8.00	SCF6125F8A	SCT6125T8A	SCF1032F8A	SCT1032T8A
7.00	○	○	○	○
6.30	SCF6125F6.3A	SCT6125T6.3A	SCF1032F6.3A	SCT1032T6.3A
6.00	○	○	○	○
5.00	SCF6125F5A	SCT6125T5A	SCF1032F5A	SCT1032T5A
4.00	SCF6125F4A	SCT6125T4A	SCF1032F4A	SCT1032T4A
3.15	SCF6125F3.15A	SCT6125T3.15A	SCF1032F3.15A	SCT1032T3.15A
3.00	SCF6125F3A	SCT6125T3A	SCF1032F3A	SCT1032T3A
2.50	SCF6125F2.5A	SCT6125T2.5A	SCF1032F2.5A	SCT1032T2.5A
2.00	SCF6125F2A	SCT6125T2A	SCF1032F2A	SCT1032T2A
1.60	SCF6125F1.6A	SCT6125T1.6A	SCF1032F1.6A	SCT1032T1.6A
1.25	○	SCT6125T1.25A	SCF1032F1.25A	SCT1032T1.25A
1.00	○	SCT6125T1A	SCF1032F1A	SCT1032T1A
0.80	○	SCT6125T800mA	○	SCT1032T800mA
0.63	○	SCT6125T630mA	○	SCT1032T630mA
0.50	○	SCT6125T500mA	○	SCT1032T500mA
0.40	○	SCT6125T400mA	○	SCT1032T400mA
0.315	○	SCT6125T315mA	○	SCT1032T315mA
0.25	○	SCT6125T250mA	○	SCT1032T250mA
0.20	○	SCT6125T200mA	○	SCT1032T200mA
0.16	○	○	○	SCT1032T160mA
0.125	○	○	○	SCT1032T125mA
0.10	○	○	○	SCT1032T100mA
U_i (VAC) Rated Voltage (VDC)	(125 ~ 350) VAC (24 ~ 125) VDC		(125 ~ 350) VAC (32 ~ 250) VDC	
Time Feature	Fast Acting	Time-Lag	Fast Acting	Time-Lag
Tube Material	Ceramic			
Standards	IEC / UL			
Breaking Capacity	50 A ~ 500 A		100 A ~ 1000 A	
Physical Size (mm)	2.7 × 2.7 × 6.3		3.2 × 3.2 × 10.3	
Product Structure	 		 